

RFJ-3TQP

Floor Jacks

SKU# 5150418

3-Ton Floor Jack, Quick Pump



VIMET CORP

H64-65 Đường Thị Giang, P. Tân Thới Nhất, Q.12, TP.HCM

Hotline: **090 998 9907** - 028 626 77 666

Email: info@vimet.com.vn - Website: www.thietbioto.vn



sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Lifts Saddle to Chassis in Just One Easy Quick Pump!

The ruggedly crafted RFJ-3TQP is a versatile quick-lifter with a 3-ton lifting capacity. Heavy steel construction and sealed hydraulics guarantee maximum durability, while the built-in safety overload valve protects personnel and equipment. If you accidentally lift a vehicle too heavy for the jack, it won't suddenly collapse on you and ruin your day. The hydraulics in the [floor jack](#) will gently descend. Since you never go under a vehicle that isn't secured on jack stands, your personal safety and the safety of your property should never be in question, even if you accidentally overload the jack.

Plus, with the exclusive "Quick-Pump" feature, this jack rises with only a single pump of the handle. Four pumps and the vehicle rises about 20" in the air. It doesn't get any faster than that! The RFJ-3TQP represents the ultimate in jacking speed and convenience. Imagine how quickly two jacks working in tandem can get you lifted for wheel service, oil changes, suspension work and more! A protective rubber sheath covers the bottom third of the extended-length handle, ensuring even low-profile vehicles aren't marred when the jack is in motion.

Of course, Ranger doesn't compromise safety for the sake of speed. The overload prevention system ensures a gentle, controlled descent in the event of weight overload placed on the jack; it's virtually impossible for the floor jack to collapse or crash to the ground. The sealed hydraulic system will never leak and is unlikely to require maintenance for as long as you own the jack.

Features

- Alloy-plated ram
- Exclusive "Quick-Pump" feature lifts saddle to chassis in one easy pump
- Welded lift arm assembly
- Heavy gauge steel construction
- Swivel casters for easy mobility
- Professional model designed for heavy use
- Heavy steel construction for maximum durability
- Sealed hydraulics prevents contamination
- Built-in safety overload system



Specifications

Lifting Capacity	6,000 lbs. (2,722 kg)
Lowered Height	5" (127 mm)
Raised Height	19.75" (502 mm)
Front Width	11" (279 mm)
Rear Width	13.5" (343 mm)
Chassis Length	25.5" (648 mm)
Shipping Weight	82 lbs. (37 kg)
Shipping Dimensions	29" x 15" x 8" (737 mm x 381 mm x 203 mm)